PROFILE - PRO



Is profiling a topic for you?

Then you've come to the right place!

Are you experts in facades & roofing?

Then our products are made for your everyday work!

Discover the world of profiling with our Austrian-made products!

Our compact, versatile machines deliver outstanding quality and efficiency for your production!

Automatic profiler for standing seam technology

Austrian quality - trusted worldwide

PROFILE PRO 3000

The luxury model:

PP3000 – The Compact Profiling System & Fully Automated Solution

Dimensions: L 1500 / W 1400 / H 1000 **Weight:** Approx. 480 kg

Profile Sizes: 25 mm & 32 mm (Clip relief), available in single and double lock

Sheet Width: Continuously adjustable via trapezoidal lead screw from 250 to 820 mm

Sheet Thickness: up to 0.8 mm max

Roller Set: State-of-the-art technology, hardened, with power transmission elements

in the rollers (rubber inserts)

Cutter System: Fully automated cross-cutting with guide rails & manually adjustable longitudinal

cutting unit with scrap ramp **Sheet Feed:** Fully automatic

Power Supply: 1.5KW / 380V / 16 Amps
Optional: Round bending unit & trailer setup
Compatible with all standard roofing materials:
Galvanized / zinc-coated zinc up to 0.7 m

up to 0.8 mm

Stainless steel ROOF-INOX / up to 0.6 mm

Uginox copper up to 0.8 mm Aluminum up to 1.0 mm

Effortless profiling of:

- Underlapping
- Overlapping
- Tapered panels (from 50 mm axle spacing)

The fully automatic solution for industrial production

- Lift-up cover (with safety switch)
- Electric rotary shear for cross-cutting before profiling
- Speed control via potentiometer from 0 15 m/min
- Option: Conversion kit for 1mm thick sheet metal
- Adjustable longitudinal cutting blade for custom panels - easy operation
- Siemens control for quantity and length selection



PROFILE- PROFI



Length measuring device (+/- 2 mm)



Sheet feed from the decoiler



Machine view with protective cover (color customizable)



Looking for more information?

Just reach out to us:

Herburger Maschinenbau GmbH,

T +43 5574 73616 | office@herburger-maschinenbau.at

Shear drive via toothed belt






Control panel and electromagnetic clutch overview



Profiling unit



PROFILINE BY HERBURGER